

### KNOCKOUT DETAIL

- NOTES: 1. KNOCKOUTS MAY BE PLACED IN BASE UNIT ABOVE CENTER OF OUTLET PIPE.
2. MINIMUM DEPTH: 3' FROM TOP OF CURB TO TOP OF KNOCKOUT. MIN. 6" FROM EDGE OF KNOCKOUT TO EDGE OF PRECAST UNIT.
3. DESIGN HYDRAULIC GRADIENT IN STORM DRAIN SYSTEM MUST BE 6" BELOW KNOCKOUT INVERT.

### GENERAL NOTES

1. UNDERDRAIN SHALL BE GROUTED IN PLACE IN THE PROVIDED KNOCKOUT OR 4"x4" HOLES (C.I.P.)
2. LIFT HOLES TO BE PROVIDED FOR HANDLING PRECAST RISER(S) AND BASE. HOLES TO BE FILLED WITH MIX #3 CONCRETE UPON INSTALLATION.
3. PRECAST JOINTS - MANUFACTURER SHALL FORM MALE AND FEMALE ENDS OF JOINTS USING THEIR OWN DESIGN. JOINTS SHALL BE SEALED & MADE WATERTIGHT BY THE CONTRACTOR USING THE MANUFACTURER'S RECOMMENDED ASTM OR AASHTO-APPROVED SEALANT.
4. ( PRECAST RISER SECTION ): 8 FT. MAXIMUM HEIGHT, 1 FT. MINIMUM .
5. ( PRECAST BASE ): 8 FT. MAXIMUM HEIGHT  
MINIMUM HEIGHT - AS NECESSARY TO PROVIDE INDICATED CLEARANCES
6. PIPE OPENINGS TO BE PROVIDED AS REQUIRED. FOR SIZE, LOCATION AND INVERT ELEVATIONS, REFER TO PLANS.
7. PLACEMENT OF SUBGRADE DRAINAGE WILL BE AS DIRECTED BY THE ENGINEER OR AS NOTED ON PLANS.
8. PRECAST WALLS: USE CAST-IN-PLACE MIX #3 CONCRETE OR BRICK TO GRADE- 2 COURSES MINIMUM, 6 COURSES MAXIMUM. INSTALL BRICK FLUSH WITH INTERIOR OF PRECAST WALL.  
PRECAST STRUCTURES MAY NOT BE BROKEN TO MEET GRADE.  
CAST-IN-PLACE WALLS: TOP 4" OF WALLS SHALL BE BRICK MASONRY.
9. GROUT AROUND ALL PIPES USING NON-SHRINK GROUT JOINT FILLER.
10. NO PART OF PIPE SHALL PASS THROUGH ANY STRUCTURE CORNER AS DEFINED BY PROJECTION OF INTERIOR WALLS. SEE DETAIL G-1. CENTER LINE PIPE ALLOWABLE RANGE:  $\pm 30^\circ$  FROM PERPENDICULAR.
11. INVERT SHALL HAVE A BENCH SIMILAR TO A TYPE A MANHOLE WHERE PIPE 24" & LARGER RUNS THROUGH INLET. SEE STD. DETAIL D-3.00
12. INVERT SHALL BE APPROVED PRECAST, PLAIN MX #3 CONCRETE OR BRICK LAID ON EDGE. INVERT TO SLOPE DOWN TOWARD OUTLET AT THE RATE OF 2" PER FOOT, OR AS SHOWN ON SPECIFIC DETAIL OR AS DIRECTED. INVERT BRICK SHALL BE ASTM C32-91 GRADE SS.
13. CAST-IN-PLACE REINFORCEMENT: SIZE & PLACEMENT AS SHOWN ON SPECIFIC DETAILS; 16" BAR LAPS; REINFORCEMENT CONTINUOUS AROUND ALL EDGES.
14. CAST-IN-PLACE STRUCTURE: 6" MIN.  
PRECAST STRUCTURE: 2" MIN.





APPROVAL  
*William H. Korman*  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
3/18/02  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**RECTANGULAR INLETS**  
**GENERAL REQUIREMENTS**

ISSUED: JANUARY, 2002  
REVISED: \_\_\_\_\_  
REVISED: \_\_\_\_\_

PLATE  
**D-2.00**



## NOTES

1. SEE STD. DETAIL D-2.00 FOR GENERAL NOTES.
2. SEE STD. DETAIL D-2.05 FOR PRECAST TOP SLAB.
3. DRAWING SHOWS PRECAST INLET. CAST-IN-PLACE INLET PER TABLE, STD. DETAIL D-2.03.
4. PREVIOUSLY STD. DETAIL D-2.00.
5. INLETS SHALL NOT BE USED IN LOCATIONS WHERE THE TOP SLAB MAY REASONABLY BE EXPECTED TO EXPERIENCE TRAFFIC LOADS.
6. DEVELOPMENT PROJECTS: CURB SECTION PAID FOR BY THE HIGHWAY CONTRACT.



APPROVAL  
*William Koppman*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS

TYPE A-1 INLET

ISSUED: OCTOBER 1977  
 REVISED: SEPTEMBER 18, 1991  
 REVISED: JANUARY 2002



PLATE

D-2.01A

2" SUPPORT FOR SIDEWALK. IF NO SIDEWALK, SEE TOP SLAB ANCHOR DETAIL ON STD. DETAIL D-2.03

SIDEWALK FRAME AND COVER

SLOPE TOP SLAB TO CONFORM TO SIDEWALK SLOPE.



## NOTES

1. SEE STD. DETAIL D-2.00 FOR GENERAL NOTES.
2. SEE STD. DETAIL D-2.05 FOR PRECAST TOP SLAB.
3. DRAWING SHOWS PRECAST INLET. CAST-IN-PLACE INLET PER TABLE, STD. DETAIL D-2.03.
4. PREVIOUSLY STD. DETAIL D-2.01.
5. INLETS SHALL NOT BE USED IN LOCATIONS WHERE THE TOP SLAB MAY REASONABLY BE EXPECTED TO EXPERIENCE TRAFFIC LOADS.
6. DEVELOPMENT PROJECTS: CURB SECTION PAID FOR BY THE HIGHWAY CONTRACT.



APPROVAL  
*William A. Appman*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE


DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS

TYPE A-2 INLET

ISSUED: OCTOBER 1977  
 REVISED: AUGUST 1997  
 REVISED: JANUARY 2002

PLATE  
 D-2.01B





## NOTES

1. SEE DETAIL D-2.00 FOR GENERAL NOTES.
2. SEE DETAIL D-2.05 FOR PRECAST TOP SLAB.
3. DRAWING SHOWS PRECAST INLET. CAST-IN-PLACE INLET PER TABLE, STD. DETAIL D-2.03.
4. PREVIOUSLY STD. DETAIL D-2.03.
5. INLETS SHALL NOT BE USED IN LOCATIONS WHERE THE TOP SLAB MAY REASONABLY BE EXPECTED TO EXPERIENCE TRAFFIC LOADS.
6. DEVELOPMENT PROJECTS: CURB SECTION PAID FOR BY THE HIGHWAY CONTRACT.




APPROVAL  
*William Hoffman*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE

## DEPARTMENT OF PUBLIC WORKS STORM DRAINAGE DETAILS TYPE B-2 INLET

ISSUED: OCTOBER 1977  
 REVISED: AUGUST, 1997  
 REVISED: JANUARY 2002


PLATE  
**D-2.02B**

SEE STD. DETAIL D-2.05, NOTE 9.



### DETAIL A FOR PRECAST A AND B INLETS

(SEE STD. DETAILS D-2.01A & B, D-2.02 A & B)



### TOP SLAB ANCHOR DETAIL (NO SIDEWALK)

	PRECAST	CAST-IN-PLACE (CIP)
W	6" MIN.	8" WIDE TO 7' DEPTH; 12" WIDE, 7' TO 10' DEPTH
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 @ 9" O/C E.W. IN BOTH FACES; 16" BAR LAPS; CONTIN- UOUS AT CORNERS
REINF. COVER	1.5 INCH MIN.	1.5 INCH MIN.
INVERT	APPROVED PRECAST, PLAIN MIX #3 CONCRETE OR BRICK	PLAIN MIX #3 CONCRETE OR BRICK
SUBGRADE OPENING	SEE DETAIL D-2.00	4" x 4" OPENINGS OR AS DIRECTED.
CONCRETE	4,500 PSI	MIX NO. 3



APPROVED  
  
 DIRECTOR  
 William Kopman  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE


### DEPARTMENT OF PUBLIC WORKS STORM DRAINAGE DETAILS TYPE A, B INLET DETAILS

ISSUED: JANUARY 2002  
 REVISED:  
 REVISED:

PLATE  
**D-2.03**

TYPE A-1

**TYPE A-2**



**TYPE B-1**

TYPE B-2

**NOTES :**

1. 4" [  $\odot$  ] 7.25 LBS. (ALL 4 SIDES OF SLAB) TO BE PRIMERED AND PAINTED WITH AN APPROVED PAINT PRIOR TO DELIVERY, WITH AN ADDITIONAL FIELD COAT APPLIED AFTER INSTALLATION.
2. SIDEWALK FRAME AND COVER - SEE STD. DETAIL D-3.06
3. 4-#6 x 36" AS SHOWN.
4. SLAB REINFORCING  
#6 BARS, 1" CLEAR  
FROM BOTTOM OF SLAB.  
#4 BARS OVER #6 BARS.
5. MIX NO. 3 CONCRETE.
6.  $3\frac{1}{4}$ " x 10" HEX HEAD BOLTS WELDED TO [ AS SHOWN ON STD. DETAIL D-2.03.
7. SEE STD. DETAIL D-2.03 FOR SECTIONAL VIEW OF TOP SLAB.
8. SLAB THICKNESS = 4"
9. 3" SCH. 40 PIPE W/THEADED END INTO 8" C.I. FLANGE @ TOP & EMBEDDED OR CORED 3" INTO GUTTER AT BOTTOM.



APPROVAL  
DIRECTOR  
William Kopman  
BUR. OF ENGINEERING/CONSTRUCTION  
3/18/02  
DATE


DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE A, B INLET  
PRECAST TOP SLABS**

ISSUED:	AUGUST, 1997
REVISED:	OCTOBER, 2001
REVISED:	


PLATE

**D-2.05**

SIZE, TYPE AND DIRECTION OF INLET CONNECTION WILL VARY TO SUIT CONDITIONS. SEE STD. DETAIL G-1.




PLAN




PLAN OF INVERT

KNOCKOUT (PRECAST) OR 4"x4" OPENING IN CAST IN PLACE STRUCTURE - 1 PER SIDE, OFFSET AS REQ'D.



SECTION X-X



SECTION Y-Y

### NOTES :

1. SEE STANDARD DETAIL D-2.00 FOR GENERAL NOTES.
2. MANHOLE STEPS - SEE DETAIL G-4.
3. PLACE 1/4" EXPANSION MATERIAL OF SAME TYPE APPROVED FOR PAVEMENT AT LOCATIONS SHOWN ON STD. DETAIL D-2.26.
4. USE COMBINATION INLET IN SUMPS IN ROAD. SEE STANDARD DETAIL D-2.07.
5. SUBGRADE DRAINAGE - 1 EACH WALL, OFFSET AS REQUIRED TO AVOID STEPS, PIPES. SEE TABLE.
6. CAST-IN-PLACE REINFORCEMENT REQUIRED ON OUTSIDE, AS WELL AS INSIDE, OF WALLS BELOW 7'-0" WHEN "H" IS GREATER THAN 7'-0". SPACING IS SAME AS FOR INSIDE OF WALL.
7. USE APPROVED BICYCLE SAFE GRATE (STD. DETAIL D-2.09A) WITHIN ALLEYS AND PUBLIC ROAD RIGHT-OF-WAY. GRATE SHOWN SHALL BE USED ONLY OUTSIDE OF THESE AREAS.

	PRECAST	CAST-IN-PLACE
A	6" MIN.	8 1/2"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 BARS @ 6"C/C EW 2" COVER (NOTE 6)
CONCRETE	4,500 PSI	MIX NO. 3
ALLOWABLE DEPTH	B.C.B.E/C APPROVAL REQUIRED OVER 15'	
SUBGRADE OPENING	AS SHOWN SEE DETAIL D-2.00	4" x 4" OPENINGS OR AS DIRECTED.



APPROVAL  
*William H. Hagan*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE


DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS

## TYPE E INLET



ISSUED: OCTOBER, 1977  
 REVISED: NOVEMBER, 2001  
 REVISED:

PLATE

D-2.06



- NOTES :
1. SEE DETAIL D-2.00 FOR GENERAL NOTES.
  2. INLET MAY BE CONSTRUCTED OF REINFORCED OR PRECAST CONCRETE. SIZE, TYPE AND DIRECTION OF INLET CONNECTION WILL VARY TO SUIT CONDITIONS. SEE STD. DETAIL G-1.
  3. CAST-IN-PLACE REINFORCEMENT REQUIRED ON OUTSIDE, AS WELL AS INSIDE, OF WALLS BELOW 7'-0" WHEN 'H' IS GREATER THAN 7'-0". SPACING IS SAME AS FOR INSIDE OF WALL.
  4. PLACE 1/4" EXPANSION MATERIAL OF SAME TYPE APPROVED FOR PAVEMENT AT LOCATIONS SHOWN ON DETAIL D-2.26.
  5. USE APPROVED BICYCLE-SAFE GRATE (DETAIL D-2.09A, SHOWN) WITHIN RIGHT-OF-WAY.
  6. SUBGRADE DRAINAGE - 1 EACH WALL - OFFSET AS REQUIRED. SEE TABLE.



	PRECAST	CAST-IN-PLACE
A	6" MIN.	8 1/2"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 BARS @ 6" O/C E.W. 2" COVER (NOTE 3)
CONCRETE	4,500 PSI	MIX NO. 3
ALLOWABLE DEPTH	B.C.B.E/C APPROVAL REQUIRED OVER 15'	
SUBGRADE OPENING	SEE DETAIL D-2.00	4" x 4" OPENINGS OR AS DIRECTED.




APPROVAL  
*William Ferguson*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
**TYPE E  
 COMBINATION INLET**


ISSUED: OCTOBER, 1977  
 REVISED: JANUARY, 1985  
 REVISED: NOVEMBER, 2001  
 PLATE

**D-2.07**


VARIABLE  
RADIUS  
MIN. 3 1/2 "



**PLAN**




**FRONT ELEVATION**



**SECTION B-B**

#3 x 10" BENT BARS WELDED  
TO L @ 16" O/C (SHOWN)  
OR

4" [ 5.4# (DETAIL D-2.10 ONLY)



NOTE:  
ALL REINFORCING  
SHALL CONFORM  
TO ASTM A-615,  
GRADE 60, AND BE  
RUST-FREE AT  
WELDS.

**SECTION A-A**

SPECIAL PREFAB CURB DETAIL

NOTE: FOR STATE HIGHWAYS USE APPROPRIATE  
CURB PIECE FROM MdSHA DETAILS.

INLET TYPE	DETAIL	THROAT WIDTH " W "	SUPPORT BEAM NOTCH
E COMB. <sup>†</sup>	D-2.07	4'-1"	OMIT
Dbl. E COMB. <sup>‡</sup>	D-2.10	8'-2"	REQUIRED
S COMB. <sup>†</sup>	D-2.18	4'-1" *	OMIT
Dbl. S COMB. <sup>†</sup>	D-2.20	5'-6 1/2"	REQUIRED

\* FOR S COMBINATION MODIFY FOR LEFT OR  
RIGHT INLET OFFSET. SEE PLAN AND SECTION  
"B-B" ON PLATE D-2.18.

† EXPOSED ANGLES TO BE GALVANIZED IN  
ACCORDANCE WITH A.S.T.M. A-123 EXCEPT  
FOR ADHERENCE WHICH SHALL BE IN  
ACCORDANCE WITH A.S.T.M. A-153.

‡ EXPOSED CHANNEL TO BE PRIMERED & PAINTED  
WITH APPROVED PAINT PRIOR TO DELIVERY.



APPROVAL  
*William K. Korman*  
DIRECTOR  
BUR. OF ENGINEERING CONSTRUCTION  
11/22/00  
DATE


DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS

**COMBINATION INLET  
CURB PIECE**


ISSUED: OCTOBER, 1977  
REVISED: JANUARY, 1985  
REVISED: AUGUST, 1997

PLATE

**D-2.08**



END VIEW



SIDE VIEW

SUPPORT BEAM

### NOTES

1. OPENINGS IN FRONT AND REAR WALLS FOR BEAM SHALL BE FILLED WITH MIX #3 CONCRETE OR BRICK (MORTARED AND SEALED ON BOTH SIDES).
2. PROVIDE DURABLE, NON-DETERIORATING SUPPORT PIECE TO ADJUST SUPPORT BEAM AND FRAME TO STREET GRADE. USE OF WOOD IS FORBIDDEN.
3. SUPPORT BEAMS SHALL BE GALVANIZED AFTER FABRICATION.

TYPE OF INLET	STD. DETAIL	CONSTRUCTION METHOD	BEAM	L	A	C
DBL E COMB.	D-2.10	PRECAST	W 5 x 19	3'-10"	1'-3"	7-1/2"
DBL E COMB.	D-2.10	CAST IN PLACE	W 5 x 19	3'-10"	1'-3"	7-1/2"
DBL S COMB.	D-2.20	PRECAST	W 8 x 21	4'-6"	1'-3"	7-1/2"
DBL S COMB.	D-2.20	CAST IN PLACE	W 8 x 21	4'-6"	1'-3"	7-1/2"





APPROVAL  
*William J. Hopman*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 4/25/02  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
**SUPPORT BEAM FOR FRAMES  
 ON DOUBLE COMBINATION INLETS**

ISSUED: APRIL 2002  
 REVISED:  
 REVISED:

PLATE  
**D-2.08A**





FRAME: PER THIS DETAIL OR PER DETAIL D-2.09




11/24/99  
DATE


## CURVED VANE (E-CV) GRATE WITH CLASS 35 TYPE E FRAME

**D-2.09A**

PROVIDE FOUNDRY NAME & FLOW DIRECTION  
AS SHOWN IN 1/2" ± [13 mm] LETTERS



SYMMETRICAL SYMMETRICAL



NOTE: ALL DIMENSIONS ARE SHOWN IN ENGLISH AND [METRIC].  
REFER TO STANDARD DETAIL PLATE D-2.10.

MATERIAL: CAST GRAY IRON ASTM A-48, CLASS 35B

WEIGHT: GRATE APPROX. 230#

GRATE SHALL SIT SQUARE UPON FRAME SUPPORTS WITHOUT  
ROCKING OR SHIFTING UNDER LOAD. GRATE SHALL MEET OR  
EXCEED AASHTO M 306 PROOF LOAD REQUIREMENTS.

FRAME: PER THIS DETAIL OR PER DETAIL D-2.09



APPROVAL  
*William J. Korman*  
DIRECTOR  
BUR. OF ENGINEERING & CONSTRUCTION  
11/24/99  
DATE


DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**DOUBLE TYPE E INLET**  
CLASS 35 FRAME WITH CURVED VANE (E-CV) GRATE

ISSUED: DECEMBER, 1997  
REVISED: \_\_\_\_\_  
REVISED: \_\_\_\_\_


PLATE  
**D-2.09B**

## NOTES


1. SEE STD. DETAIL D-2.00 FOR GENERAL NOTES.
2. INLET MAY BE CONSTRUCTED OF REINFORCED OR PRECAST CONCRETE. SIZE, TYPE & DIRECTION OF INLET CONNECTIONS WILL VARY TO SUIT CONDITIONS. SEE DETAIL G-1.
3. USE CURVED VANE GRATE (D-2.09B) AS SHOWN WITHIN ROAD RIGHT-OF-WAY.
4. PLACE 1/4" EXPANSION MATERIAL OF SAME TYPE APPROVED FOR PAVEMENT AT LOCATIONS SHOWN ON DETAIL D-2.26.
5. MIN. 6" CLEAR BETWEEN SUPPORT BEAM & PIPES IN FRONT OR REAR WALL.
6. SUBGRADE DRAINS - 2 EA. IN FRONT & REAR WALL - SEE TABLE
7. INLET FRAME SUPPORT BEAMS - SEE STD. DETAIL D-2.08A



**COMBINATION INLET CURB PIECE  
(FRONT ELEVATION)**



**PLAN**



**SECTION A-A**

	PRECAST	POURED-IN-PLACE
B	8" MIN.	8 1/2"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 @ 10" O/C E.W. IN $\phi$ OF WALLS. **
CONCRETE	4,500 PSI	MIX NO. 3
ALLOWABLE DEPTH	B.C.B.E/C APPROVAL	REQUIRED IF H > 12'
SUBGRADE OPENING	SEE DETAIL D-2.00	4" x 4" OPENINGS OR AS DIRECTED.

\*\* REINFORCING CONTINUOUS AT CORNERS.  
ALL LAPS 1' - 4".




APPROVAL  
DIRECTOR  
*William K. ...*  
BUR. OF ENGINEERING/CONSTRUCTION  
3/18/02  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**DOUBLE TYPE E  
COMBINATION INLET**

ISSUED: OCTOBER, 1977  
REVISED: JANUARY, 1985  
REVISED: NOVEMBER, 2001

PLATE

**D-2.10**



## NOTES

1. CONCRETE TO BE 4500 PSI.
2. REINFORCING-2 LAYERS OF 4x4-W4.0xW4.0 WELDED WIRE FABRIC.
3. THREADED PLASTIC INSERTS TO BE PROVIDED FOR HANDLING.
4. GRADE AND SLOPE ADJUSTMENTS TO BE COMPLETED IN THE FIELD USING CONCRETE MIX NO.6.
5. PIPE OPENINGS TO BE PROVIDED AS REQUIRED. FOR SIZE, LOCATION, AND INVERT ELEVATIONS REFER TO THE PLANS.
6. PLACEMENT OF SUBGRADE DRAINAGE WILL BE AS DIRECTED BY THE ENGINEER OR AS NOTED ON THE PLANS.
7. MANHOLE STEPS SHALL BE IN ACCORDANCE WITH STANDARD DETAIL G-4.
8. 5" THICK PRECAST TOP SLAB, CONCRETE TO BE 4500 PSI. PLACE LAYER OF 4x4-W4.0x W4.0 WELDED WIRE FABRIC OR NO.4 DEFORMED BARS 6" C/C 2 WAYS.
9. FIELD-CONSTRUCT THIS PORTION OF INLET USING BRICK MASONRY OR REINFORCED CONCRETE MIX #6. REINFORCE WITH TWO LAYERS OF 4x4-W4.0xW4.0 WELDED WIRE FABRIC OR NO. 4 DEFORMED BARS 6" C/C EACH WAY.
10. SEE STANDARD DETAIL D-2.00 FOR GENERAL NOTES.




APPROVAL  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
7/24/06  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
PRECAST STANDARD  
TYPE H COMBINATION INLET

ISSUED: JUNE, 2006  
REVISED:  
REVISED:

PLATE  
D-2.12






APPROVAL  
*Charles T. Allen*  
 DIRECTOR  
*William R. Brown*  
 BUR. OF ENGINEERING/CONSTRUCTION  
 10/23/97  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
**TYPE J INLET**  
 WITH MODIFIED GRATE

ISSUED: AUGUST, 1997  
 REVISED:  
 REVISED:

PLATE  
**D-2.13**

REV. MAY 1997 J.T.V.



SEE DETAIL D-2.13 FOR OTHER VIEWS AND FOR GRATE DETAILS.




APPROVAL  
DIRECTOR  
*William J. Ryan*  
BUR. OF ENGINEERING/CONSTRUCTION  
11/24/99  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE J INLET**  
WITH MODIFIED GRATE

ISSUED: AUGUST, 1997  
REVISED:  
REVISED:

PLATE  
**D-2.14**







PRECAST KNOCKOUT OR OPENING - SEE NOTE 6. OFFSET AS REQ'D TO AVOID DRAIN PIPES AND STEPS.

GENERAL NOTES 11, 12


SEE STD. DETAIL G-2 (PRECAST)




FOR UNDEPRESSED INLETS, USE NORMAL PAVEMENT SLOPE. FOR DEPRESSED INLETS, SEE STANDARD DETAIL D-2.26.



SECTION A-A



SECTION B-B ADJACENT TO CURB



SECTION A-A ADJACENT TO CURB

## NOTES

- SEE STD. DETAIL D-2.00 FOR GENERAL NOTES. SEE TABLE ON STD. DETAIL D-2.16B FOR INFORMATION REGARDING CONCRETE, REINFORCING, ALLOWABLE DEPTH AND SUBGRADE OPENINGS FOR PRECAST & CIP INLETS.
- INLET MAY BE CONSTRUCTED OF PRECAST OR REINFORCED CONCRETE (SEE TABLE, DETAIL D-2.16B). SIZE, TYPE AND DIRECTION OF INLET CONNECTION WILL VARY TO SUIT CONDITIONS. SEE STD. DETAIL G-1.
- THIS INLET SHALL NOT BE USED IN ROADWAY SUMPS. USE EQUIVALENT (D-2.18) OR LARGER COMBINATION INLET AT A SUMP WITHIN ROAD RIGHT-OF-WAY.
- PLACE APPROVED 1/4" EXPANSION MATERIAL FOR PAVEMENT AT LOCATIONS SHOWN ON DETAIL D-2.26.
- INLET MAY BE USED IN MEDIAN DITCHES OR AS A YARD INLET, WITH OR WITHOUT A CONCRETE COLLAR. SEE STD. DETAIL D-2.16B. PARALLEL BAR GRATE (STD. DETAIL D-2.17) SHALL BE USED IN THESE APPLICATIONS, UNLESS OTHERWISE DIRECTED ON PLANS OR BY THE ENGINEER.
- SUBGRADE DRAINAGE - 1 EACH WALL. OFFSET AS REQUIRED TO AVOID STEPS, PIPES. SEE TABLE ON STANDARD DETAIL D-2.16B.
- CAST-IN-PLACE REINFORCEMENT REQUIRED ON OUTSIDE & INSIDE OF WALLS BELOW 7'-0" WHEN 'H' IS GREATER THAN 7'-0". SPACING IS SAME AS FOR INSIDE OF WALL.
- USE APPROVED BICYCLE-SAFE GRATE (SEE DETAIL D-2.21A) WITHIN ALLEYS & PUBLIC ROAD R/W.




APPROVAL  
*William Hopman*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE

# DEPARTMENT OF PUBLIC WORKS STORM DRAINAGE DETAILS TYPE S INLET SINGLE GRATE

ISSUED: OCTOBER, 1977  
 REVISED: AUGUST, 1997  
 REVISED: NOVEMBER, 2001

PLATE


D-2.16A




NOTE: THE CONCRETE MEDIAN DITCH TO BE USED IN CONNECTION WITH THIS INLET WILL BE WARPED FROM THE STANDARD SECTION TO MEET THE SECTION AT THE END OF THE INLET. THIS TRANSITION WILL TAKE PLACE WITHIN A DISTANCE OF TEN FEET FROM THE INLET. PAVING WITHIN TEN FEET OF THE INLET TO BE INCLUDED IN THE UNIT PRICE BID FOR THE INLET.

FOR INLET IN SUMP, MODIFY SLOPES AS SHOWN IN THE ISOMETRIC VIEW ON DETAIL PLATE D-2.19B


**ISOMETRIC VIEW**  
MEDIAN DITCH APPLICATION




**SECTION B-B**  
MEDIAN DITCH APPLICATION



**SECTION A-A**  
MEDIAN DITCH APPLICATION




**SECTION B-B**  
YARD INLET APPLICATION



**SECTION A-A**  
YARD INLET APPLICATION

MIX #2 CONCRETE  
WITH 6" x 6" -  
W2.1 x W2.1 WWF



**PLAN VIEW**  
OPTIONAL CONCRETE  
COLLAR

W = 2' OR AS SHOWN ON PLANS

REFER TO NOTES 1 THROUGH 7 ON DETAIL D-2.16A.

	PRECAST	CAST-IN-PLACE
A	6" MIN.	8 1/2"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 BARS @ 6" O/C E.W. 2" COVER. SEE NOTE 7 ON DETAIL D-2.16A
CONCRETE	4,500 PSI	MIX NO. 3
ALLOWABLE DEPTH	B.C.B.E/C APPROVAL REQUIRED OVER 15'	
SUBGRADE OPENINGS	SEE DETAIL D-2.00	4" x 4" OPENINGS OR ALTERNATE AS DIRECTED



APPROVAL  
*William Hopman*  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
3/18/02  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE S INLET**  
**SINGLE GRATE**  
**YARD & MEDIAN APPLICATIONS**


ISSUED: AUGUST, 1997  
REVISED: OCTOBER, 2001  
REVISED:

PLATE

**D-2.16B**


SEE NOTE 'A'

GRATE SHOWN SHALL BE USED ONLY FOR INLETS LOCATED OUTSIDE OF PUBLIC ROAD R/W. USE APPROVED BICYCLE-SAFE GRATE (D-2.21A) WITHIN RIGHT-OF-WAY.




NOTE 'A'  
FRAME TO BE CASTING WITH FLANGE CUT AS SHOWN, WHEN FRAME IS TO BE USED ADJACENT TO CURB OPENING.


NOTE : CASTING MATERIALS SHALL BE GRAY IRON.



SECTION B-B



SECTION C-C



SECTION D-D






APPROVAL  
*William J. [Signature]*  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
11/22/00  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE S INLET**  
**SINGLE FRAME & GRATE**

ISSUED: OCTOBER, 1977  
REVISED: AUGUST, 1997  
REVISED:

PLATE  
**D-2.17**

Gusseted Rear Flange for Grate-Only Applications (See Details D-2.16A and B)  
Rear Flange for Combination Inlets (See Detail D-2.18)



NOTE: ALL DIMENSIONS ARE SHOWN IN ENGLISH AND [METRIC].  
MATERIAL: CAST GRAY IRON ASTM A-48, CLASS 35B  
WEIGHT: GRATE APPROX. 338#/EA., FRAME APPROX. 182#/EA.  
FRAME: PER THIS DETAIL OR PER DETAIL D-2.17



APPROVAL  
*William J. [Signature]*  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
5/8/01  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**SINGLE TYPE S FRAME (CLASS 35)**  
WITH CURVED VANE (S-CV) GRATES




ISSUED: DECEMBER, 1997  
REVISED: APRIL, 2001  
REVISED:

PLATE  
**D-2.17A**



# NOTES

1. SEE STD. DETAIL D-2.00 FOR GENERAL NOTES.
2. INLET MAY BE CONSTRUCTED OF PRECAST OR REINFORCED CONCRETE. SIZE, TYPE AND DIRECTION OF INLET CONNECTION WILL VARY TO SUIT CONDITIONS. SEE DETAIL G-1.
3. PLACE 1/4" EXPANSION MATERIAL OF SAME TYPE APPROVED FOR PAVEMENT AT LOCATIONS SHOWN ON STD. DETAIL D-2.26, & BETWEEN THE FRAME AND ABUTTING RIGID PAVEMENT.
4. SUBGRADE DRAINAGE - 1 EACH WALL. OFFSET AS REQ'D. TO AVOID STEPS, PIPES. SEE TABLE.
5. CAST-IN-PLACE REINFORCEMENT REQUIRED ON OUTSIDE, AS WELL AS INSIDE, OF WALLS BELOW 7'-0" WHEN 'H' IS GREATER THAN 7'-0". SPACING IS SAME AS FOR INSIDE OF WALL.
6. SUPPORT BEAM SHALL NOT BE USED.
7. USE APPROVED BICYCLE-SAFE GRATE (STD. DETAIL D-2.21A) WITHIN ALLEYS AND PUBLIC ROAD RIGHT-OF-WAY.
8. INLET MAY BE USED IN MEDIAN DITCHES OR AS A YARD INLET, WITH OR WITHOUT A CONCRETE COLLAR. SEE STD. DETAIL D-2.19B. USE PARALLEL BAR GRATE (STD. DETAIL D-2.21) FOR YARD AND MEDIAN INLETS OUTSIDE OF PUBLIC ROAD RIGHT-OF-WAY.
9. TYPE 'S' INLET - DOUBLE GRATE TANDEM MAY BE USED WITH ONE END ADJACENT TO CURB. FRAME WILL BE LAID ON NORMAL SLOPE OF ROADWAY UNLESS NOTED OTHERWISE. ORIENT FRAMES & GRATES AS REQUIRED TO COLLECT RUNOFF. FRAME & GRATE DIMENSIONS SAME AS WHEN SIDE IS ADJACENT TO CURB AS SHOWN ON LEFT.
10. THIS INLET SHALL NOT BE USED IN ROADWAY SUMPS. USE A COMBINATION INLET (STD. DETAIL D-2.20) AT A SUMP WITHIN ROAD RIGHT-OF-WAY.



	PRECAST	POURED-IN-PLACE
A	6" MIN.	8 1/2"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 BARS @ 6" C/C E.W. 2" COVER. SEE NOTE 5.
CONCRETE	4,500 PSI	MIX NO. 3
ALLOWABLE DEPTH	B.C.B.E/C APPROVAL REQUIRED OVER 15'	
SUBGRADE OPENINGS	SEE DETAIL D-2.00	4" x 4" OPENINGS OR ALTERNATE AS DIRECTED




APPROVED  
*William Kopman*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
**TYPE S INLET**  
**DOUBLE GRATE TANDEM**  
**(NO SUPPORT BEAM)**


ISSUED: OCTOBER, 1977  
 REVISED: NOVEMBER, 2001  
 REVISED:

PLATE

**D-2.19A**




**ISOMETRIC VIEW**  
MEDIAN DITCH APPLICATION




**SECTION B-B**  
MEDIAN DITCH APPLICATION

TYPE S DOUBLE GRATE TANDEM  
FRAME AND GRATE  
SEE DETAIL D-2.21




**SECTION A-A**  
MEDIAN DITCH APPLICATION




**SECTION B-B**  
YARD INLET APPLICATION

TYPE S DOUBLE GRATE TANDEM  
FRAME AND GRATE  
SEE DETAIL D-2.21



**SECTION A-A**  
YARD INLET APPLICATION

MIX #2 CONCRETE  
WITH 6" x 6" -  
W2.1 x W2.1 WWF



**PLAN VIEW**  
OPTIONAL CONCRETE  
COLLARS

W = 2' OR AS SHOWN ON PLANS

REFER TO NOTES 1 THROUGH 8 ON DETAIL D-2.19A.

	PRECAST	POURED-IN-PLACE
A	6" MIN.	8 1/2"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 BARS @ 6" C/C E.W. 2" COVER; SEE NOTE 5 ON STD. DETAIL D-2.19A
CONCRETE	4,500 PSI	MIX NO. 3
ALLOWABLE DEPTH	B.C.B.E/C APPROVAL REQUIRED OVER 15'	
SUBGRADE OPENINGS	SEE DETAIL D-2.00	4" x 4" OPENINGS OR ALTERNATE AS DIRECTED




APPROVAL  
DIRECTOR  
*William R. Koppman*  
BUR. OF ENGINEERING/CONSTRUCTION  
3/18/02  
DATE


DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE S INLET**  
**DOUBLE GRATE TANDEM**  
**YARD & MEDIAN APPLICATIONS**

ISSUED: AUGUST, 1997  
REVISED: NOVEMBER, 2001  
REVISED:

PLATE  
**D-2.19B**




PRECAST CONCRETE CURB  
SEE STD. DETAIL D-2.08



SECTION B-B

- NOTES**
1. SEE STD. DETAIL D-2.00 FOR GENERAL NOTES.
  2. INLET MAY BE CONSTRUCTED OF PRECAST OR REINFORCED CONCRETE. SIZE, TYPE AND DIRECTION OF INLET CONNECTION WILL VARY TO SUIT CONDITIONS. SEE STANDARD DETAIL G-1.
  3. CAST-IN-PLACE REINFORCEMENT REQUIRED ON OUTSIDE, AS WELL AS INSIDE, OF WALLS BELOW 7'-0" WHEN 'H' IS GREATER THAN 7'-0". SPACING IS SAME AS FOR INSIDE OF WALL.
  4. PLACE 1/4" EXPANSION MATERIAL OF SAME TYPE APPROVED FOR PAVEMENT AT LOCATIONS SHOWN ON STANDARD DETAIL D-2.26, AND BETWEEN FRAME & ABUTTING RIGID PAVEMENT.
  5. SUBGRADE DRAINAGE - 1 OPENING PER SIDE. OFFSET AS REQ'D. SEE TABLE.
  6. USE APPROVED BICYCLE-SAFE GRATE (STD. DETAIL D-2.21A) WITHIN ROAD RIGHT-OF-WAY.
  7. PIPE OPENINGS IN FRONT OR REAR WALL OF INLET SHALL MAINTAIN 6" MINIMUM CLEARANCE TO SUPPORT BEAM.



SECTION A-A

SEE STD. DETAIL G-2  
(PRECAST)  
BACKFILL ALL SIDES (SEE  
STD. DETAIL D-2.00)

	PRECAST	POURED-IN-PLACE
A	6" MIN.	8 1/2"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 BARS @ 6" C/C E.W. 2" COVER. SEE NOTE 3
CONCRETE	4,500 PSI	MIX NO. 3
ALLOWABLE DEPTH	B.C.B.E/C APPROVAL REQUIRED OVER 15'	
SUBGRADE OPENINGS	SEE DETAIL D-2.00	4" x 4" OPENINGS OR ALTERNATE AS DIRECTED




APPROVAL  
*William Hopman*  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
3/18/02  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE S COMBINATION  
INLET DOUBLE GRATE TANDEM**

ISSUED: OCTOBER, 1977  
REVISED: JANUARY, 1985  
REVISED: NOVEMBER, 2001


PLATE

**D-2.20**







### METHOD OF ANCHORING SUPPORT BEAM

(IF INLET IS  
CONSTRUCTED  
OF BRICK.)



GRATE SHOWN SHALL BE USED  
ONLY FOR INLETS LOCATED  
OUTSIDE OF PUBLIC ROAD R/W.  
USE CURVED VANE GRATE  
OR OTHER APPROVED BICYCLE-  
SAFE GRATE WITHIN RIGHT-  
OF-WAY.



DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS

## TYPE S INLET & COMBINATION FRAME & GRATE

ISSUED: OCTOBER, 1977  
REVISED: AUGUST, 1997  
REVISED:

PLATE




D-2.21



APPROVAL  
DIRECTOR  
William R. Spang  
BUR. OF ENGINEERING/CONSTRUCTION  
11/24/99  
DATE

REV. FEBRUARY 1998 J.A.V.

PROVIDE FOUNDRY NAME & FLOW DIRECTION  
AS SHOWN IN 1/2"± [13 mm±] LETTERS



NOTE: ALL DIMENSIONS ARE SHOWN IN ENGLISH AND [METRIC].  
MATERIAL: CAST GRAY IRON ASTM A-48, CLASS 35B  
WEIGHT: GRATE APPROX. 338#  
GRATE SHALL SIT SQUARE UPON FRAME SUPPORTS WITHOUT  
ROCKING OR SHIFTING UNDER LOAD. GRATE SHALL MEET OR  
EXCEED AASHTO HS20 LOAD STANDARDS.  
FRAME: PER DETAIL D-2.21B OR DETAIL D-2.21




APPROVAL  
*William J. [Signature]*  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
11/24/99  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**CURVED VANE (S-CV) GRATE**  
FOR TYPE S INLET FRAMES

ISSUED: AUGUST, 1997  
REVISED: \_\_\_\_\_  
REVISED: \_\_\_\_\_

PLATE  
**D-2.21A**




APPROVAL  
 DIRECTOR  
 William J. Ryan  
 BUR. OF ENGINEERING/CONSTRUCTION  
 11/24/99  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
**DOUBLE TYPE S FRAME (CLASS 35)**  
 WITH CURVED VANE (S-CV) GRATES


ISSUED: AUGUST, 1997  
 REVISED:  
 REVISED:

PLATE  
**D-2.21B**



## CROSS SECTION

	PRECAST	CAST-IN-PLACE (CP)
W	6" MINIMUM	8" MINIMUM
REINF.	2 LAYERS- 4x4 W4.0 x W4.0 - WWF	#4 @ 9" O/C E.W. IN BOTH FACES; 16" BAR LAPS; CONTINUOUS AT CORNERS
REINF. COVER	1.5 INCH MIN.	1.5 INCH MIN.
INVERT	APPROVED PRECAST, PLAIN MIX #3 CONCRETE OR BRICK	PLAIN MIX #3 CONCRETE OR BRICK
SUBGRADE OPENING	SEE DETAIL D-2.00	4" x 4" OPENINGS OR AS DIRECTED.
CONCRETE	4,500 PSI	MIX NO. 3



## SECTION A-A

## NOTES

1. SEE GENERAL NOTES, STANDARD DETAIL D-2.00.
2. SEE DETAIL D-2.22B FOR PRECAST TOP SLAB AND OPTIONAL CONCRETE COLLAR DETAIL.
3. FOR PIPE SIZE, LOCATION AND INVERT ELEVATIONS, REFER TO PLANS. USE 24" MAXIMUM DIAMETER PIPE OUTFALL WITH STRUCTURE SHOWN. CONSTRUCT INLET HEADPIECE OVER TYPE A MANHOLE STRUCTURE WHERE 27" OR LARGER DRAIN PIPES ARE REQUIRED. SHOW HEADPIECE DETAIL ON PLANS IN THIS CASE.
4. THIS INLET SHALL NOT BE USED ADJACENT TO PUBLIC ROADS OR ALLEYS NOR IN ANY LOCATION WHERE VEHICLES COULD ENCOUNTER IT.
5. OPENINGS TO BE PLACED IN ANY OR ALL SIDES AS DIRECTED BY ENGINEER OR ON PLANS. OPENING LIP ELEVATION TO BE SET IN THE FIELD.
6. PRECAST RISER TO BE REPLACED AT CONTRACTOR'S EXPENSE IF TOP SLAB SUPPORTS ARE BROKEN.



APPROVAL  
 DIRECTOR  
 William Kogman  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/18/02  
 DATE


DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
 TYPE Y-1 INLET

ISSUED: OCTOBER 1977  
 REVISED: SEPTEMBER 16, 1991  
 REVISED: MARCH 2002



PLATE

D-2.22A

# TOP SLAB:



# CONCRETE COLLAR: (IF INDICATED ON PLANS)



W = 2'-0" OR AS INDICATED ON CONSTRUCTION DRAWING.






APPROVAL  
DIRECTOR  
*William Kypman*  
BUR. OF ENGINEERING / CONSTRUCTION  
3/18/02  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE Y-1 INLET**  
DETAILS

ISSUED: AUGUST, 1997  
REVISED: MARCH, 2002  
REVISED:

PLATE

**D-2.22B**



	PRECAST	CAST-IN-PLACE (CIP)
W	6\"	8\"
REINF.	2 LAYERS- 4x4 W4.0 x W4.0- WWF	#4 @ 9\"
REINF. COVER	1.5 INCH MIN.	1.5 INCH MIN.
INVERT	APPROVED PRECAST, PLAIN MIX #3 CONCRETE OR BRICK	PLAIN MIX #3 CONCRETE OR BRICK
SUBGRADE OPENING	SEE DETAIL D-2.00	4\"
CONCRETE	4,500 PSI	MIX NO. 3

## NOTES

1. SEE GENERAL NOTES, STANDARD DETAIL D-2.00.
2. USE MIX #2 CONCRETE FOR CONCRETE APRON.
3. FOR PIPE SIZE, LOCATION AND INVERT ELEVATIONS, REFER TO PLANS. USE 24\"
4. PRECAST RISER TO BE REPLACED AT CONTRACTOR'S EXPENSE IF TOP SLAB SUPPORTS ARE BROKEN.
5. OPENINGS TO BE PLACED IN ANY OR ALL SIDES AS DIRECTED BY ENGINEER OR ON PLANS. SUPPORT FRAME ABOVE OPENING ON 2\"
6. CAST IRON CURVED VANE GRATES OR CAST IRON PARALLEL BAR GRATES SHALL BE USED WITH CAST IRON FRAME FOR THIS APPLICATION. SEE STD. DETAILS D-2.17, D-2.17A.



APPROVAL  
*[Signature]*  
 DIRECTOR  
*[Signature]*  
 BUR. OF ENGINEERING/CONSTRUCTION  
 3/10/05  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
**ALTERNATE Y-1 INLET**



ISSUED: JANUARY, 2005  
 REVISED:  
 REVISED:

PLATE  
**D-2.22C**



**NOTE :**

SEE DETAIL PLATE  
D-2.22A FOR ALL DATA  
NOT SHOWN.



**NOTE :**

INLET TO BE USED IN SUMP. MAXIMUM DESIGN CAPACITY  $Q = 3.0$  CFS.  
TO BE USED WITH 15" RCCP MINIMUM, 24" RCCP MAXIMUM CONNECTION.  
NOT TO BE USED IN ROADWAY OR ADJACENT TO PARKING OR DRIVEWAY  
AREA. NOT FOR USE ADJACENT TO WOODED AREAS DUE TO POSSIBLE  
DEBRIS BLOCKAGE. USE OF PRECAST OR CAST-IN-PLACE Y-1 INLET  
(D-2.22A) IS REQUIRED FOR OTHER SWALE CONDITIONS.




APPROVAL  
*William J. [Signature]*  
DIRECTOR  
BUR. OF ENGINEERING/CONSTRUCTION  
5/15/02  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS  
**TYPE Y-3 INLET**  
WITH Y-1 INLET BASE, BEEHIVE GRATE

ISSUED: AUGUST, 1997  
REVISED: MAY, 2002  
REVISED:

PLATE  
**D-2.24A**



**NOTE:**

INLET TO BE USED IN SUMP, MAXIMUM DESIGN CAPACITY Q= 3.0 CFS. TO BE USED WITH 15" RCCP CONNECTION. NOT TO BE USED IN ROADWAY OR ADJACENT TO PARKING OR DRIVEWAY AREAS. CONNECTIONS SHALL BE LIMITED AS SHOWN ON DETAIL D-2.23. NOT FOR USE ADJACENT TO WOODED AREAS DUE TO POSSIBLE DEBRIS BLOCKAGE.



APPROVAL  
*Charles J. Gillen*  
 DIRECTOR  
*William J. ...*  
 BUR. OF ENGINEERING / CONSTRUCTION  
 10/23/97  
 DATE


DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS  
**TYPE Y-3 YARD INLET**  
 TYPE Y-2 BASE, BEEHIVE GRATE

ISSUED: AUGUST, 1997  
 REVISED:  
 REVISED:


PLATE  
**D-2.24B**

**NOTE :**

SEE DETAIL PLATE  
D-2.22A FOR ALL DATA  
NOT SHOWN.



**SECTION A - A**



**NOTE :** INLET TO BE USED IN SUMP. MAXIMUM DESIGN CAPACITY  $Q = 3.0$  CFS.  
TO BE USED WITH 15" RCCP MINIMUM, 24" RCCP MAXIMUM CONNECTION.  
NOT TO BE USED IN ROADWAY OR ADJACENT TO PARKING OR DRIVEWAY  
AREA. NOT FOR USE ADJACENT TO WOODED AREAS DUE TO POSSIBLE  
DEBRIS BLOCKAGE. USE OF PRECAST OR CAST-IN-PLACE Y-1 INLET  
(D-2.22A) REQUIRED FOR OTHER SWALE CONDITIONS.




APPROVAL  
DIRECTOR  
*William D. [Signature]*  
BUR. OF ENGINEERING/CONSTRUCTION  
DATE 5/15/02

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS


**TYPE Y-4 INLET**  
WITH Y-1 INLET BASE, STOOL GRATE

ISSUED: AUGUST, 1997  
REVISED: MAY, 2002  
REVISED:

PLATE  
**D-2.25A**



30" DIA. RCCP CL3, 4 OR 5 MAY BE SUBSTITUTED FOR BASE SHOWN.




**TYPE Y-4 INLET**  
WITH Y-2 INLET BASE, STOOL GRATE



**D-2.25B**



# PLAN



## SECTION A - A



## SECTION B - B

5'-0" CURB SHALL BE TRANSITION SECTION WHERE ADJACENT CURB & GUTTER ISN'T USED OR IS MOUNTABLE (R-21).

SEE STANDARD DETAILS D-2.00 THROUGH D-2.03 FOR GUTTER DEPRESSIONS AT TYPE A & B INLETS



APPROVAL  
*William Kopman*  
 DIRECTOR  
 BUR. OF ENGINEERING/CONSTRUCTION  
 4/10/01  
 DATE

DEPARTMENT OF PUBLIC WORKS  
 STORM DRAINAGE DETAILS


**GUTTER DEPRESSION  
 & FLARE AT E & S INLETS**

ISSUED: OCTOBER 1977  
 REVISED: AUGUST, 1997  
 REVISED: MARCH, 2001

PLATE

**D-2.26**

FORM 200 2-83



## CROSS-SECTION

## NOTES

1. APPLICABLE TO TYPE E, TYPE S AND DOUBLE TYPE S GRATE & COMBINATION INLETS. DOUBLE TYPE E AND CURB OPENING INLETS REQUIRE A SPECIAL DETAIL.
2. SLAB TO BE OF MIX #3 CONCRETE WITH #5 REBARS @ 6" O/C EACH WAY.
3. BACKFILL OVER SLAB WITH FLOWABLE FILL OR SELECT BORROW AS DIRECTED BY THE ENGINEER. WHERE ACCESS MUST BE MAINTAINED, SET 24" STD. HEAVY TRAFFIC FRAME & COVER TO GRADE ATOP SLAB MODIFIED WITH 24" OPENING.



APPROVED  
*[Signature]*  
DIRECTOR  
*[Signature]*  
BUR. OF ENGINEERING/CONSTRUCTION  
3/10/05  
DATE

DEPARTMENT OF PUBLIC WORKS  
STORM DRAINAGE DETAILS

## INLET CAPPING

ISSUED: DECEMBER, 2004  
REVISED:  
REVISED:

PLATE

D-2.46